

Reifenausschlussliste 2020 (Div. I / Street)

Avon	ACB10, CR500, CR6ZZ, ZZR, ZZS, CR28 Sport, Tech R (RA), RX
BF-Goodrich	g-force R1
Bridgestone	RE11S, RE55S, RE520S, RE540S
Colway (Markgum)	N-Rally / Formula 2, Intermediate
Continental	ContiForceContact
DMACK	DMT1, DMT 3, DMT-RC
Dunlop	D01J, Direzza 03G (02G), D83J (93J, 98J), CR 311, SP Sport R7, Sport Maxx Race, Super Sport Race
Falken	Azenis Sport (RS)
Federal	FZ-201, FZ-202, Federally T-10
Fedima	F/N, F/T
Goodyear	Eagle F1 Supersport R, Eagle F1 Supersport RS
Hankook	Z205, Z206, Z207, Z209, Z210, Z213, Z214, Z217, Ventus TD (Z221), Ventus RSS
Hoosier	alle Modelle
Indy Sport	TR
Interstate	Race DNRT
Kumho	ECSTA V70A (V700), CO3, W700, TW01, TW02
Lassa	Racing
Marangoni	Zeta Racing, Zeta Linea Sport
Markgum-Colway	N-Rally / Formula 2, Intermediate
Matador	SM1, SM2, SM3, SM5, SM10, Rain, Rain-Plus
Maxxis	ZR 9
Maxsport	RB4, RB5
Michelin	Pilot Sport Cup (TW 80), Pilot Sport P01, TB5 (F, R), TB 15, PB 20, XAS-FF
Nankang	NS-2R Track 120 Soft, AR-1
Nitto	NT01, NT555, NT05R, NT555R, NT555RII
Pirelli	RE, RK, RX, P Zero C, P Zero Corsa, P Zero Trofeo R, P7 Corsa, Sport Intermediate
Silverstone	FTZ RR, FTZ Sport, S-575, S-585
Toyo	Proxes R888(R), R881, R08R, Proxes RA-1
Yokohama	ADVAN A006, A008, A021, A032, A033, A035, A038, A039, A048, A052
Zestino	alle Modelle

Der Treadwear-Faktor (Verschleißwert) muss mindestens 140 betragen.
Ausnahmen ab 2020 sind zu beachten: Yokohama A052 (TW200).

Reifen ohne Verschleißangaben dürfen verwendet werden, sofern sie nicht auf der Ausschlussliste stehen.

Zulässige Semi-Slicks 2020 (Div. II)

Avon	ACB10; ZZR; ZZS; CR500; CR6 ZZ; CR28 Sport
Bridgestone	RE11S
Continental	ContiForceContact
Dunlop	Direzza 03G; Sport Maxx Race
Extreme	VR1, VR2, VR3
Federal	FZ 201
Goodyear	Eagle F1 Supersport R, Supersport RS
Hankook	Ventus TD (Z221), Z207, Z217
Interstate	Race DNRT
Kumho	ECSTA V70A, W700
Michelin	Pilot Sport Cup (+), Pilot Sport Cup 2 (1)
Nankang	AR-1, NS-2R Track 120
Pirelli	P Zero Trofeo R; P7 Corsa
Toyo	Proxes R888, R888R
Yokohama	ADVAN A048, A052

Neben den angeführten Semi-Slicks dürfen alle handelsüblichen Reifen eingesetzt werden, die auch in der Division I zulässig sind.